

Alpen Steel | Renewable Energy

Alpen Steel

Multicrystalline 120/24

[Call for Pricing](#)

ELECTRICAL CHARACTERISTIC	: AS-120/24
Maximum power (Pmax)	: 120W
Voltage at Pmax (Vmp)	: 34.4V
Current at Pmax	: 3.49A
Open-circuit voltage (Voc)	: 43.2V
Short-Circuit current (Isc)	: 3.86A
Temperature coefficient of Voc	: (0.065±0.015)%/ °C
Temperature coefficient of Isc	: -(80±10)mV/°C
Temperature coefficient of power	: -(0.5±0.05)%/ °C
NOCT (Air 20c, Sun 0.8kW/m)	: 47±2°C
Operating Temperature	: -40°C to 85°C
Maximum system voltage	: 600V DC
Power tolerance	: ± 5%
<i>*STC: Irradiance 1000W/m, AM1.5 spectrum, module temperature 25 C</i>	
°C	°C

SPECIFICATION	AS-120/24
Cells	: Multicrystalline silicon solar cell
No. of cells and connections	: 72(4X18)
Module Dimension	: 1499mm[59.02in.]x672mm[26.46in.]x40mm[1.58in.]
Weight	: 11.65kg[25.68lbs]

** Specifications are subject to change without notice at any time.*

[Vendor Information](#)