

## Alpen Steel | Renewable Energy

*Alpen Steel*

### Multicrystalline130/24

[Call for Pricing](#)

<b>ELECTRICAL CHARACTERISTIC</b>	<b>: AS-130/12</b>
Maximum power (Pmax)	: 130W
Voltage at Pmax (Vmp)	: 34.4V
Current at Pmax	: 3.78A
Open-circuit voltage (Voc)	: 43.2V
Short-Circuit current (Isc)	: 4.18A
Temperature coefficient of Voc	: (0.065±0.015)%/ °C
Temperature coefficient of Isc	: -(80±10)mV/°C
Temperature coefficient of power	: -(0.5±0.05)%/ °C
NOCT (Air 20c, Sun 0.8kW/m)	: 47±2°C
Operating Temperature	: -40°C to 85°C
Maximum system voltage	: 600V DC
Power tolerance	: ± 5%

\*STC:Irradiance 1000W/m, AM1.5 spectrum, module temperature 25 C

<b>SPECIFICATION</b>	<b>AS-130/12</b>
Cells	: Multicrystalline silicon solar cell
No. of cells and connections	: 72(4X18)
Module Dimension	: 1616mm[63.63in.]x672mm[26.46in.]x40mm[1.58in.]
Weight	: 13.2kg [29.10lbs]

\* Specifications are subject to change without notice at any time.

[Vendor Information](#)