

## Alpen Steel | Renewable Energy

Alpen Steel

### Multicrystalline 150/24

[Call for Pricing](#)

<b>ELECTRICAL CHARACTERISTIC</b>	<b>: AS-150/24</b>
Maximum power (Pmax)	: 150W
Voltage at Pmax (Vmp)	: 34.4V
Current at Pmax	: 4.36A
Open-circuit voltage (Voc)	: 43.2V
Short-Circuit current (Isc)	: 4.85A
Temperature coefficient of Voc	: $(0.065 \pm 0.015)\% / ^\circ\text{C}$
Temperature coefficient of Isc	: $-(80 \pm 10)\text{mV} / ^\circ\text{C}$
Temperature coefficient of power	: $-(0.5 \pm 0.05)\% / ^\circ\text{C}$
NOCT (Air 20c, Sun 0.8kW/m)	: $47 \pm 2 ^\circ\text{C}$
Operating Temperature	: $-40 ^\circ\text{C}$ to $85 ^\circ\text{C}$
Maximum system voltage	: 600V DC
Power tolerance	: $\pm 5\%$
<i>*STC: Irradiance 1000W/m, AM1.5 spectrum, module temperature 25 C</i>	
Â	Â

<b>SPECIFICATION</b>	<b>AS-145/24</b>
Cells	: Multicrystalline silicon solar cell
No. of cells and connections	Â 72(6X12)
Module Dimension	Â 1250mm[49.22in.]x992mm[39.06in.]x50mm[1.97in.]
Weight	: 15.1kg[33.20lbs]

*\* Specifications are subject to change without notice at any time.*

[Vendor Information](#)