

Alpen Steel | Renewable Energy

Alpen Steel

Multicrystalline 155/24

[Call for Pricing](#)

ELECTRICAL CHARACTERISTIC	: AS-155/24
Maximum power (Pmax)	: 155W
Voltage at Pmax (Vmp)	: 45.5V
Current at Pmax	: 4.05A
Open-circuit voltage (Voc)	: 43.2V
Short-Circuit current (Isc)	: 5.01A
Temperature coefficient of Voc	: $(0.065 \pm 0.015)\% / ^\circ\text{C}$
Temperature coefficient of Isc	: $-(80 \pm 10)\text{mV} / ^\circ\text{C}$
Temperature coefficient of power	: $-(0.5 \pm 0.05)\% / ^\circ\text{C}$
NOCT (Air 20c, Sun 0.8kW/m)	: $47 \pm 2 ^\circ\text{C}$
Operating Temperature	: $-40 ^\circ\text{C}$ to $85 ^\circ\text{C}$
Maximum system voltage	: 600V DC
Power tolerance	: $\pm 5\%$
<i>*STC: Irradiance 1000W/m, AM1.5 spectrum, module temperature 25 C</i>	
Â	Â

SPECIFICATION	AS-145/24
Cells	: Multicrystalline silicon solar cell
No. of cells and connections	Â 72(6X12)
Module Dimension	Â 1292mm[50.87in.]x992mm[39.06in.]x50mm[1.97in.]
Weight	: 15.6kg[34.39lbs]

** Specifications are subject to change without notice at any time.*

[Vendor Information](#)