

Alpen Steel | Renewable Energy

Alpen Steel

Multicrystalline 170/24

[Call for Pricing](#)

ELECTRICAL CHARACTERISTIC	: AS-170/24
Maximum power (Pmax)	: 170W
Voltage at Pmax (Vmp)	: 34.4V
Current at Pmax	: 4.94A
Open-circuit voltage (Voc)	: 43.2V
Short-Circuit current (Isc)	: 5.49A
Temperature coefficient of Voc	: (0.065±0.015)%/ °C
Temperature coefficient of Isc	: -(80±10)mV/°C
Temperature coefficient of power	: -(0.5±0.05)%/ °C
NOCT (Air 20c, Sun 0.8kW/m)	: 47±2°C
Operating Temperature	: -40°C to 85°C
Maximum system voltage	: 600V DC
Power tolerance	: ± 5%
<i>*STC:Irradiance 1000W/m, AM1.5 spectrum, module temperature 25 C</i>	
Â	Â

SPECIFICATION	AS-170/24
Cells	: Multicrystalline silicon solar cell
No. of cells and connections	Â 72(6X12)
Module Dimension	Â 1406mm[55.35in.]x992mm[39.06in.]x50mm[1.97in.]
Weight	: 17.5kg[38.58lbs]

** Specifications are subject to change without notice at any time.*

[Vendor Information](#)